PV module - ISL 144 NM10R 595

Manufacturer	INOX SOLAR LIMITED	**Commercial data**	
Model	ISL 144 NM10R 595	Data source :TUV RHEINLAND (INIDIA) PVT. LTD.	
Pnom STC power (manufacturer)	595 Wp	Technology	Si-mono
Module size (W x L)	1.134 x 2.278 m²	Rough module area (Amodule)	2.58 m²
Number of cells	2 x 72	Sensitive area (cells) (Acells)	2.38 m²

Specifications for the model (manufacturer or measurement data)

Reference temperature (TRef)	25 °C	Reference irradiance (GRef)	1000 W/m²
Open circuit voltage (Voc)	51.8 V	Short-circuit current (Isc)	14.56 A
Max. power point voltage (Vmpp)	43.0 V	Max. power point current (Impp)	13.82 A
=> maximum power (Pmpp)	594.7 W	Isc temperature coefficient (muIsc)	5.6 mA/°C

One-diode model parameters

Shunt resistance (Rshunt)	350 Ω	Diode saturation current (IoRef)	0.018 nA
Serie resistance (Rserie)	0.20 Ω	Voc temp. coefficient (MuVoc)	-117 mV/°C
Specified Pmax temper. coeff. (muPMaxR)	-0.28 %/°C	Diode quality factor (Gamma)	1.02
		Diode factor temper. coeff. (muGamma)	0.000 1/°C

Reverse Bias Parameters, for use in behaviour of PV arrays under partial shadings or mismatch

Reverse characteristics (dark) (BRev)	3.20 mA/V²	(quadratic factor (per cell))	
Number of by-pass diodes per module	1	Direct voltage of by-pass diodes	-0.7 V

Model results for standard conditions (STC: T=25 °C, G=1000 W/m², AM=1.5)

Max. power point voltage (Vmpp)	43.0 V	Max. power point current (Impp)	13.85 A
Maximum power (Pmpp)	594.7 Wp	Power temper. coefficient (muPmpp)	-0.28 %/°C
Efficiency(/ Module area) (Eff_mod)	23.0 %	Fill factor (FF)	0.788
Efficiency(/ Cells area) (Eff_cells)	24.9 %		

PV module: INOX SOLAR LIMITED, ISL 144 NM10R 595

